

MOTORCYCLE LITHIUM BATTERY



*This for illustration only. The detail refer to specification.



5x

Low-Temperature Cranking Power



10x

Faster Recharging



10x

Stronger Engine Starting Performance



High Rate

Premium LiFePO₄ Cells



5 Years

Extended Service Life



Built-in BMS

Multi-Layer Protection, Smarter Management



1/3 Weight

Ultra-Light vs. Lead-Acid



60c

High Current Start @25°C

MOTORCYCLE LITHIUM BATTERY



Model	Voltage	Capacity	Power	CCA	CA	Dimension(±3mm)			Weight	Terminal	Cycle Life
	V	Ah	Wh	A	A	L	W	H	Kg,±3%	Number direction	
MKS-MC12020F	12	2	24	60	120	112	69	85	0.46	four-terminal	2000
MKS-MC12020T	12	2	24	60	120	112	69	85	0.47	- +	2000
MKS-MC12025F	12	2.5	30	75	150	112	69	85	0.52	four-terminal	2000
MKS-MC12025T	12	2.5	30	75	150	112	69	85	0.55	- +	2000
MKS-MC12030T	12	3	36	90	180	112	69	85	0.56	- +	2000
MKS-MC12030F	12	3	36	90	180	112	69	85	0.57	four-terminal	2000
MKS-MC12035F	12	3.5	42	105	210	112	69	85	0.65	four-terminal	2000
MKS-MC12035T	12	3.5	42	105	210	112	69	85	0.65	- +	2000
MKS-MC12040F	12	4	48	120	240	112	69	85	0.69	four-terminal	2000
MKS-MC12040T	12	4	48	120	240	149	65	93	0.76	- +	2000
MKS-MC12050F	12	5	60	150	300	149	86	93	0.97	four-terminal	2000
MKS-MC12050T	12	5	60	150	300	149	86	93	0.91	- +	2000
MKS-MC12060F	12	6	72	180	360	149	86	93	0.99	four-terminal	2000
MKS-MC12060T	12	6	72	180	360	149	86	93	1.06	- +	2000
MKS-MC12080F	12	8	96	240	480	149	86	130	1.27	four-terminal	2000
MKS-MC12080T	12	8	96	240	480	149	86	130	1.34	- +	2000
MKS-MC12120F	12	12	144	360	720	174	86	155	1.97	four-terminal	2000
MKS-MC12180F	12	18	216	540	1080	165	125	175	2.96	four-terminal	2000

Explanation: CCA is -10 degrees 30C3S, CA is room temperature 60C3S



Motorcycle



Scooter



ATV



Jet SKI



Lawn Mower



Snowmobile